

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
27 October 2005 (27.10.2005)

PCT

(10) International Publication Number
WO 2005/100029 A2

(51) International Patent Classification⁷:

B41J

(74) Agents: TANI, Yoshikazu et al.; 6-20, Akasaka 2-chome,
Minato-ku, Tokyo, 1070052 (JP).

(21) International Application Number:

PCT/JP2005/007576

(22) International Filing Date: 14 April 2005 (14.04.2005)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

2004-118984

14 April 2004 (14.04.2004) JP

(71) Applicant (for all designated States except US): CANON
KABUSHIKI KAISHA [JP/JP]; 3-30-2, Shimomaruko,
Ohta-ku, Tokyo, 1468501 (JP).

(72) Inventors; and

(75) Inventors/Applicants (for US only): SUZUKI, Toru
[JP/JP]; c/o CANON KABUSHIKI KAISHA, 3-30-2,
Shimomaruko, Ohta-ku, Tokyo, 1468501 (JP). KUDO,
Kiyomitsu [JP/JP]; c/o CANON KABUSHIKI KAISHA,
3-30-2, Shimomaruko, Ohta-ku, Tokyo, 1468501 (JP).
KUDO, Satoshi [JP/JP]; c/o CANON KABUSHIKI
KAISHA, 3-30-2, Shimomaruko, Ohta-ku, Tokyo,
1468501 (JP). TSUJIMOTO, Akira [JP/JP]; c/o CANON
KABUSHIKI KAISHA, 3-30-2, Shimomaruko, Ohta-ku,
Tokyo, 1468501 (JP).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG,
KM, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ,
TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA,
ZM, ZW.


(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,
SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN,
GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— without international search report and to be republished
upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: INK CARTRIDGE



(57) Abstract: The present invention makes it possible to improve the alignment accuracy of the joint section of an ink cartridge with an ink supply route of an inkjet head. Based on this, the present invention provides an ink cartridge capable of preventing ink leakage with high reliability and constructed inexpensively in a reduced size and particularly suitable for a pit-in system. To attain this, distance (L1) is set to be shorter than distance (L2), where the distance (L1) is the one between a joint section (145) positioned in the proximity of a front surface (1A) of an ink cartridge (1) and an engage reference portion (135)

serving as a reference position when the ink cartridge (1) is installed in the inkjet printing apparatus; and the distance (L2) is the one between the front surface (1A) of the ink cartridge (1) and the engage reference portion (135).

WO 2005/100029 A2